

Test Tubes

I. APPLICATIONS

1. Used for multiple laboratory procedures

II. TUBE FEATURES

1. Materials: Premium polystyrene and Polypropylene
2. Transparent glass-like clarity permits easy viewing of tube contents
3. Working temperature: PS: stable from -20°C to 60°C, PP: -20°C to 121°C
4. Tested to withstand centrifugation of 5,800 RCF

III. TUBE DESIGN

1. Round bottom tube
2. PS: Clearly visible with either clear or turbid samples

IV. CAP DESIGN

1. Materials: Polyethylene
2. Plug style closure

V. PACKAGING

1. Tubes
 - a) Bulk packaged, 2,000 tubes/case
2. Caps
 - a) Bulk packaged, 1,000 caps/case

VI. DESCRIPTION

Item	Size	Packaging	Material	Sterile
12-1275	12x75mm tube	500 /bag, 4 bags/case	PS	No
12-2275	12x75mm tube	500 /bag, 4 bags/case	PP	No
12-1299	12mm Cap	250 /bag, 8 bags/case	PE	No
12-1300	13x100mm tube	1000 /bag, 2 bags/case	PS	No
12-1399	13mm Cap	1000 /bag, 2 bags/case	PE	No

VII. STERILITY

1. N/A

VIII. CERTIFICATION

Biologix products are manufactured completely according to the TUV ISO 9001:2008 standard.

IX. RESTRICTIONS

Refer to the Chemical Resistance Chart in our catalog, and available within our online catalog.

X. PRODUCT PARAMETER

Dimensions=mm

Cat #	Description	A	B	C	D	E	F	G
12-1275	Tube	75.0	O.D 12.0	O.D. 10.3	-	-	-	-
12-2275	Tube	75.0	O.D 12.0	O.D. 10.3	-	-	-	-
12-1299	Cap	-	-	-	O.D. 11.7	O.D. 9.6	19.3	7.8
12-1300	Tube	100.0	O.D. 13.0	O.D. 11.0	-	-	-	-
12-1399	Cap	-	-	-	O.D. 11.0	8.5	17.5	-

